



ScopeVAULT
by ClinicalChoice

ScopeVault™ with Dri-Scope® 10-Port Manifold
Technical Data Sheet





SCOPEVAULT™ with Dri-Scope® 10-Port Manifold Installed

Part No: SV-DRI

Materials of Construction	
Frame and Related Components	Anodized aluminum extrusion, powder-coated aluminum, acrylic panels, formed plastics
Endoscope Cradles	PETG, ABS, or other formed plastics
Dimensions and Other Specifications	
Overall weight	250 lbs. (113.39 kg)
Dimensions	94" H x 29" W x 23" D
Temperature Specifications	Room temperature should be between 60° and 68° degrees Fahrenheit.
Filtration	24/7 HEPA Filtered Air-Flow (2) Filters Installed
Fan Specification	(4) Six-Inch diameter brushless fans maintain up to 1,000 cubic feet per minute air flow
Lighting	LED Lighting – door activated upon opening/closing
Drip Tray	Removable Drip Tray, even with door closed
Electrical Requirements	120V, 20-amp Circuit, Full Load Draw: 10 amps
Electrical Cord (NEMA Plug Configuration 125V 5-15R)	10-foot cord with left- and right-side positioning holes towards the top of the cabinet.
Seismic Information	Seismic Mounting Brackets available
Cleaning	Compatible with Hydrogen Peroxide wipes and non-ammonia-based products.
Other	Designed for indoor use only. Cabinet height is 94". Requires a minimum of 96" ceiling height for installation without removing ceiling tiles.

Dri-Scope Aid®, Dri-Scope Aid® Ten Port Manifold System, and the Dri-Scope Aid® Cabinet system are registered trademarks of TRICOR Systems, Inc.